



APPLICATION

- Use for general purpose
- laid on cable trays / Cable ladder
- Install in duct in ground or direct burial in ground

TESTING VOLTAGE : 2,500 Volts

REFERENCE STANDARD :

TIS 11 PART 101-2559, TABLE 3

CABLE STRUCTURE

CONDUCTOR : Annealed Solid or Stranded Copper

CLASS 1 & 2 Size 1 - 500 mm²

INSULATION : Polyvinyl chloride type PVC/C

SHEATHED : Polyvinyl chloride type PVC/ST4

CORE IDENTIFICATION :

Single core, color as request

CLASSIFICATION

Maximum Conductor Temperature : 70°C

Circuit Voltage does not exceed

450/750 Volts (U₀/U)

450 Volts between Line to Earth (U₀)

750 Volts between Line to Line (U)

Technical Data



TIS 11 PART 101-2559, TABLE 3

Nominal cross sectional area	Conductor type	Minimum number of wires	Nominal insulation thickness	Nominal sheathed thickness	Maximum overall diameter	Maximum conductor resistance at 20°C	Minimum insulation resistance at 70°C	Current rating		Cable weight (approx.)	Standard packing
								on cable ladder at 40°C	direct burial in ground at 30°C		
mm ²	Class	No.	mm	mm	mm	Ω/km	MΩ·km	A	A	kg/km	m
1	1	1	1.5	1.8	8.6	18.1	0.0207	-	21	80	100/C
1	2	7	1.5	1.8	8.8	18.1	0.0200	-	21	80	100/C
1.5	1	1	1.5	1.8	9.0	12.1	0.0184	-	26	85	100/C
1.5	2	7	1.5	1.8	9.2	12.1	0.0175	-	26	90	100/C
2.5	1	1	1.5	1.8	9.4	7.41	0.0157	-	35	100	100/C
2.5	2	7	1.5	1.8	9.8	7.41	0.0146	-	35	110	100/C
4	1	1	1.5	1.8	10.0	4.61	0.0135	-	45	120	100/C
4	2	7	1.5	1.8	10.5	4.61	0.0124	-	45	130	100/C
6	2	7	1.5	1.8	11.0	3.08	0.0107	-	57	160	100/C
10	2	7	1.5	1.8	12.0	1.83	0.0088	-	76	210	500/D
16	2	7	1.5	1.8	13.0	1.15	0.0074	-	99	280	500/D
25	2	7	1.5	1.8	14.5	0.727	0.0061	127	128	390	500/D
35	2	7	1.5	1.8	16.0	0.524	0.0053	157	154	490	500/D
50	2	19	1.5	1.8	17.0	0.387	0.0046	191	181	620	500/D
70	2	19	1.5	1.8	19.0	0.268	0.0039	244	223	850	500/D
95	2	19	1.7	1.8	21.5	0.193	0.0038	297	267	1,110	500/D
120	2	37	1.7	1.8	23.0	0.153	0.0034	345	304	1,400	500/D
150	2	37	1.9	2.0	26.0	0.124	0.0034	397	342	1,700	500/D
185	2	37	2.1	2.0	28.0	0.0991	0.0034	453	386	2,100	500/D
240	2	37	2.3	2.2	31.5	0.0754	0.0033	535	448	2,700	500/D
300	2	61	2.5	2.2	35.0	0.0601	0.0032	617	507	3,400	500/D
400	2	61	2.7	2.2	38.5	0.0470	0.0030	741	577	4,300	500/D
500	2	61	3.1	2.4	43.0	0.0366	0.0031	854	654	5,400	500/D

Conductor Class 1 : Solid

Class 2 : Stranded

C : Packing in coil

D : Packing in drum

การใช้งาน

- ใช้งานทั่วไป
- วางบนรางเคเบิล
- ร้อยท่อฝังดินหรือฝังดินโดยตรง

www.ssupercable.com